














Analytical Balance -Touch Screen  
**MAB 220T**

-  EMFC Electro Magnetic Force Compensation
-  Touch Screen display
-  Percentage Weighing
-  Multiple Weighing Units
-  Density Determination Function
-  RS232C Interface
-  Counting Weighing mode
-  Underhook Weighing
-  Calibration with Internal weight
-  Time
-  Date



## Analytical Balance -Touch Screen

MODEL	MAB 220T (Touch screen)
Max. ( Capacity )	220 g
Readability ( d )	0.0001 g
Repeatability ( ± )	0.2 mg
Linearity ( ± )	0.4 mg
Min. (Capacity)	10 mg
Verification Scale Intervals (e)	1 mg
Calibration	Motorized Internal Calibration
Class	Class I
Display	5 inch Touch Screen
Make	WENSAR
Response Time	4 - 5 Sec
Pan Size (mm)	80 mm
Tare Range	Full
Operating Temperature	±15°C to ± 25°C
Sensitivity Drift ±	2ppm / °C
Density	Function Available
Key Sound	Yes
Weighing Chamber	240 x 190 x 265 mm
Unit	g, mg, ct, oz
Baud rate Options	1200, 2400, 4800, 9600
Interface	RS232C
Power Supply	AC 220V / 50-60 Hz
Dimension (LxWxH) mm	475 x 315 x 485
Weight	10 Kg

**SPECIFICATIONS**

★ Specifications are subject to change without notice.

Density Determination Kit for solid samples available - optional